

**Model Variations**

EV2360-BK: with Flex Stand, black  
EV2360-WT: with Flex Stand, white  
EV2360-FBK: without stand, black  
EV2360-FWT: without stand, white



Note: Flex Stand is removable

**Panel****Type**

IPS

**Backlight**

LED

**Size**

22.5" (57.2 cm)

**Native Resolution**

1920 x 1200 (16:10 aspect ratio)

**Viewable Image Size (H x V)**

488.2 x 297.2 mm

**Pixel Pitch (H x V)**

0.254 x 0.248 mm

**Pixel Density**

101 ppi

**Display Colors**

16.77 million

**Viewing Angles (H / V, typical)**

178° / 178°

**Brightness (typical)**

250 cd/m<sup>2</sup>

**Contrast Ratio (typical)**

1000:1

**Response Time (typical)**

5 ms (gray-to-gray)

**Color Gamut (typical)**

sRGB

**Video Signals****Input Terminals**

DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), D-Sub mini 15 pin

**Digital Scanning Frequency (H / V)**

DisplayPort: 31 - 75.5 kHz / 59 - 61 Hz  
HDMI: 31 - 75.5 kHz / 49 - 51 Hz, 59 - 61 Hz

**Analog Scanning Frequency (H / V)**

31 - 75.5 kHz / 59 - 61 Hz

**Sync Formats**

Separate

**USB****Upstream**

USB 5Gbps: Type-B

**Downstream**

USB 5Gbps: Type-A x 2

**Audio****Speakers**

1.0 W + 1.0 W

**Input Terminals**

Stereo mini jack, DisplayPort, HDMI

**Output Terminals**

Headphones (Stereo mini jack)

**Power****Power Input**

AC 100 - 240 V, 50 / 60 Hz

**Typical Power Consumption**

11 W

<b>Maximum Power Consumption</b>	37 W
<b>Power Save Mode</b>	0.5 W or less
<b>Features &amp; Functions</b>	
<b>Preset Modes</b>	User1, User2, sRGB, Paper, Movie, DICOM
<b>Automatic Brightness Control</b>	Auto Eco View
<b>OSD Languages</b>	English, German, French, Italian, Japanese, Simplified Chinese, Spanish, Swedish, Traditional Chinese
<b>Physical Specifications</b>	
<b>Dimensions (Landscape, W x H x D)</b>	499 x 333.9 - 473.9 x 233 mm
<b>Dimensions (Without Stand, W x H x D)</b>	499 x 321.3 x 53.6 mm
<b>Net Weight</b>	5.5 kg
<b>Net Weight (Without Stand)</b>	3.4 kg
<b>Height Adjustment Range</b>	140 mm
<b>Tilt</b>	35° Up, 5° Down
<b>Swivel</b>	344°
<b>Pivot</b>	90° (both clockwise and counterclockwise)
<b>Hole Spacing (VESA Standard)</b>	100 x 100 mm
<b>Environmental Requirements</b>	
<b>Operating Temperature</b>	5 - 35°C
<b>Operating Humidity (R.H., non-condensing)</b>	20 - 80%
<b>Certifications &amp; Standards (Please contact EIZO for the latest information.)</b>	TCO Certified Generation 9, EPEAT 2018 (US), TUV/Ergonomics, TUV/Low blue light content, TUV/Flicker Free, TUV/GS, RCM, CE, UKCA, CB, cTUVus, FCC-B, CAN ICES-3 (B), TUV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, EAC
<b>Dedicated Software</b>	
<b>Monitor Control Utility Screen In Style</b>	Supported
<b>Signal Cables</b>	DisplayPort (2 m)
<b>Others</b>	AC power cord (2 m), USB Type-A - USB Type-B cable (2 m), VESA mounting screw x 4, setup guide
<b>Warranty</b>	5 Years <a href="#">Zero bright sub-pixels for six months from date of purchase.</a>
<b>Dimension Drawing</b>	<a href="#">PDF</a>

- <sup>2</sup> With current LCD / OLED technology, a panel may contain a limited number of missing or flickering pixels.
- <sup>5</sup> If the monitor is left on continuously over a long period of time, dark smudges or burn-in may appear. To maximize the life of the monitor, we recommend the monitor be turned off periodically.